

# digiLED iMAG-R



From the thoroughbred range of digiLED hi-res LED rental products comes the latest edition, the iMAG-R Series . Enhanced features including the digiLED fast-rig mechanism for quick build-ups and tear-downs, and robust mechanics with front/rear serviceability for extreme fast swap of components make iMAG the perfect product for life on the road. And when it comes to rugged good looks, the iMAG-R is in a class of it's own with breathtaking image quality for a complete proven cost-effective indoor solution.

# MODULE SPECIFICATIONS - digiLED iMAG-R

		iMAG-R 2600	iMAG-R 3200	iMAG-R 3900	iMAG-R 4600	iMAG-R 5200
<b>LEDS</b>						
LEDS Per Pixel		1R1G1B				
Red Wavelength (Dominant)	nm	620				
Green Wavelength (Dominant)	nm	520				
Blue Wavelength (Dominant)	nm	465				
<b>PIXELS</b>						
Pixel Configuration		SMD 3-in-1				
LED Face Colour		Black body				
LEDS Per Area	LED/module	110,592	73,008	49,152	34,992	27,648
Physical Pixel Pitch	mm	2.604	3.205	3.906	4.63	5.208
Physical Pixel Resolution (Width)	pixels/module	192	156	128	108	96
Physical Pixel Resolution (Height)	pixels/module	192	156	128	108	96
Physical Pixel Resolution (Total)	pixels/module	36,864	24,336	16,384	11,664	9,216
Physical Pixels Per Area	pixels/m2	147,456	97,344	65,536	46,656	36,864
<b>MODULE</b>						
Standard Active Module Width	mm	500				
Standard Active Module Height	mm	500				
Standard Active Module Area	m2	0.25				
Module Depth	mm	105	105	100	100	100
Module Weight	kg	9	9	8	8	8
LED Tile Width	mm	250				
LED Tile Height	mm	250				
Viewing Angle - Horizontal	degrees	>140	>140	>140	>140	>140
Viewing Angle - Vertical	degrees	>160	>140	>140	>140	>140
Ingress Protection	(Front)	IP54				
Ingress Protection	(Back)	IP54				
Surface Finish		Aluminium				
LED Fixings		Front or rear access				
Storage Temperature Range	degree C	-10 to +40				
Operating Temperature Range	degree C	-10 to +40				
Operating Humidity Range	%	10 to 90 Non-condensing				
<b>COLOUR</b>						
Processing Depth colours		16bit				
Refresh Rate	Hz	>2,500	>1,900	>2,000	>2,000	>2,000
LED Driven Scanning		1/24	1/16	1/16	1/9	1/8
<b>BRIGHTNESS</b>						
Brightness (After Calibration)	nits	>900	>1,100	>1,100	>1,100	>1,100
Brightness Control		Auto/Manual				
Contrast ratio		4,000:1	4,000:1	4,000:1	4,000:1	4,000:1
<b>POWER</b>						
Input Voltage	VAC	110-230				
Input Power (Average)	watts/m2	168	180	138	180	144
Input Power (Maximum)	watts/m2	560	600	460	600	480
<b>OTHER</b>						
Lifespan	hours	>100,000				
Computer System Type		PC Win7, Vista, XP, WIN2000				
Video Input		DVI, HDMI				
Connection Method		HSYV				
Connectors		USB and RJ45				
Control System		digiLED Navigator NV				
Remote Diagnostics		Yes (on all major components) (alerts via email/SMS)				
Certification		CE, EMC Class A, (TUV), ETL, RoHS				

All specifications are correct at time of print, however they are liable to change and should be confirmed at point of order



# digiled iMAG-R Module Information



REAR



FRONT

100 - 105mm

500mm

500mm

